

Liberica Native Image Kit 25.0.1-2 (25.0.1+14) Installation Guide



Liberica NIK
25.0.1
November, 2025

be//soft

Copyright © BellSoft Corporation 2018-2025.

BellSoft software contains open source software. Additional information about third party code is available at https://bell-sw.com/third_party_licenses. You can also get more information on how to get a copy of source code by contacting info@bell-sw.com.

THIS INFORMATION MAY CHANGE WITHOUT NOTICE. TO THE EXTENT PERMITTED BY APPLICABLE LAW, BELLSOFT PROVIDES THIS DOCUMENTATION “AS IS” WITHOUT WARRANTY OF ANY KIND, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT. IN NO EVENT WILL BELLSOFT BE LIABLE TO YOU OR ANY THIRD PARTY FOR ANY LOSS OR DAMAGE, DIRECT OR INDIRECT, FROM THE USE OF THIS DOCUMENTATION, INCLUDING WITHOUT LIMITATION, LOST PROFITS, LOST INVESTMENT, BUSINESS INTERRUPTION, GOODWILL, OR LOST DATA, EVEN IF BELLSOFT IS EXPRESSLY ADVISED IN ADVANCE OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The use of any software product referenced in this document is governed by the applicable license agreement, which is not modified in any way by the terms of this notice.

Alpaquita, Liberica and BellSoft are trademarks or registered trademarks of BellSoft Corporation. The registered trademark Linux® is used pursuant to a sublicense from the Linux Foundation, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis. Java and OpenJDK are trademarks or registered trademarks of Oracle and/or its affiliates. Other trademarks are the property of their respective owners and are used only for identification purposes.

Contents

1. Introduction 5

2. Apple macOS 6

Installing DMG bundle on Apple macOS 6

Installing ZIP bundle on macOS 8

Liberica NIK dependencies on macOS 9

3. Linux 10

Installing DEB and RPM packages 10

Installing standalone NIK package on GNU/Linux 10

Liberica NIK dependencies on Linux 11

4. Alpine Linux 12

Installing APK package on Alpine Linux 12

Installing standalone NIK package on Alpine Linux 12

Liberica NIK dependencies on Alpine Linux 13

5. Microsoft Windows 14

Installing with Microsoft Windows Installer package 14

Installing standalone package on Microsoft Windows 16

Liberica NIK dependencies on Windows 16

6. Installing language packages 17

7. Verifying downloaded files 18

Windows 18

Apple macOS 18

Linux 18

1. Introduction

This document provides installation instructions for Liberica NIK in different operating systems.

You can download Liberica NIK from either the [Liberica JDK Download Center](#) or, as a support-plan customer, via a link on the [support portal](#). After you log in to the support portal, you can see a direct link to the version of Liberica product you requested under Technologies. If you use the Liberica Download Center page, scroll down and select the NIK version, OS, and [package type](#). After the download is finished, you can [verify](#) the downloaded file by comparing its size on your drive to the size on the Downloads page.

**Note:**

The installer screens are provided for information purpose only and may vary in different releases.


2. Apple macOS

Installing DMG bundle on Apple macOS


1. To run the installer, double-click the file you have downloaded.
2. Double-click the pkg icon to open the **Install Liberica NIK Wizard**.




3. Click **Continue** on the Welcome screen.
4. Optionally, you can change the installation location. Press **Install** to proceed.



5. Confirm new software installation. The files will start copying immediately.



6. Once the installation is complete, press **Close** to exit the installation wizard.



Liberica NIK 25.0.1 is installed to the `/Library/Java/LibericaNativeImageKit/liberica-vm-25.0.1-openjdk25/` directory, or another directory with a similar name in `/Library/Java/LibericaNativeImageKit`, depending on the selected version of the JDK and package type (core, standard, or full). You can use the `$NIK_HOME` environment variable to store the path to the installed package: `/Library/Java/LibericaNativeImageKit/liberica-vm-25.0.1-openjdk25/Contents/Home/`.

Installing ZIP bundle on macOS

1. To install Liberica NIK, download the .zip package.

```
curl -O https://download.bell-sw.com/vm/25.0.1/bellsoft-liberica-vm-  
openjdk25.0.1+14-25.0.1+2-macos-amd64.zip
```

2. After the download is finished, unpack the file.

```
unzip bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-macos-amd64.zip  
sudo mv bellsoft-liberica-vm-openjdk25-25.0.1  
/Library/Java/LibericaNativeImageKit/
```


This will unpack Liberica NIK to `/Library/Java/LibericaNativeImageKit/`. Either add `Contents/Home/bin` subdirectory to `$PATH`, or remember `/Library/Java/LibericaNativeImageKit/bellsoft-liberica-vm-openjdk25-25.0.1/Contents/Home/` as the `$NIK_HOME` environment variable.

To uninstall Liberica NIK, simply remove its directory and unset the related environmental variables.

Liberica NIK dependencies on macOS

xcode is required for Liberica Native Image Kit. Install the necessary tools with the following command:

```
xcode-select --install
```

3. Linux

Installing DEB and RPM packages

Download either `.rpm` or `.deb` package.

Install the package using the appropriate package manager. See the example for Apt:

```
sudo apt install ./bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-linux-  
amd64.deb
```

Or for an RPM-base system:

```
sudo yum install ./bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-linux-  
amd64.rpm
```

The package is installed to `/opt/bellsoft/liberica-vm-25.0.1-openjdk25/`.

For scripting purposes, we recommend adding the `${NIK_HOME}` environment variable that points to your Liberica Native Image Kit installation directory.

Installing standalone NIK package on GNU/Linux

To install Liberica NIK, download the `.tar.gz` package.

Unpack it with the following command.

```
export INSTALL_DIR=<your directory>  
tar -C $INSTALL_DIR -xzf bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-linux-  
amd64.tar.gz
```

This will unpack Liberica NIK to the selected directory. Either add `$INSTALL_DIR/bellsoft-liberica-vm-openjdk25-25.0.1/bin` to `$PATH`, or remember `$INSTALL_DIR/bellsoft-liberica-vm-openjdk25-25.0.1` as the `$NIK_HOME` environment variable.

To uninstall Liberica NIK, simply remove this directory and unset the related environmental variables.

Liberica NIK dependencies on Linux

Several libraries are required for Liberica Native Image Kit on Linux systems. Install these libraries on Debian-based systems with the following command:

```
sudo apt install g++ make zlib1g-dev
```

Installed components also have additional libraries dependencies, such as TruffleRuby depends on `libssl-dev`.

You can use a similar command to install dependencies on rpm-based systems. See this example for Rocky Linux:

```
sudo yum install gcc-c++ make zlib-devel
```

Other types of Linux systems may require different packages.

4. Alpine Linux

Installing APK package on Alpine Linux

Download the .apk package.

Install the package using the appropriate package manager. See our example for Apt:

```
# Add public key to check signature
wget -P /etc/apk/keys/ https://apk.bell-sw.com/info@bell-sw.com-
5fea454e.rsa.pub
# Install package
sudo apk add ./bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-linux-x64-
musl.apk
```

The package is installed to /opt/bellsoft/liberica-vm-25.0.1-openjdk25/.

For scripting purposes, we recommend adding the `${NIK_HOME}` environment variable which would point to your Liberica Native Image Kit installation directory.

Installing standalone NIK package on Alpine Linux

To install Liberica NIK, download the .tar.gz package.

```
wget https://download.bell-sw.com/vm/25.0.1/bellsoft-liberica-vm-
openjdk25.0.1+14-25.0.1+2-linux-x64-musl.tar.gz
```

Unpack it with the following command.

```
export INSTALL_DIR=<your directory>
tar -C $INSTALL_DIR -xzf bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-linux-
x64-musl.tar.gz
```

This will unpack Liberica NIK to the selected directory. Either add `$INSTALL_DIR/bellsoft-liberica-vm-openjdk25-25.0.1/bin` to `$PATH`, or remember `$INSTALL_DIR/bellsoft-liberica-vm-openjdk25-25.0.1` as the `$NIK_HOME` environment variable.

To uninstall Liberica NIK, simply remove this directory and unset the related environmental variables.

Liberica NIK dependencies on Alpine Linux

Several libraries are required for Liberica Native Image Kit on Alpine Linux. Install these libraries with the following command:


```
sudo apk add bash g++ make zlib-static
```

Installed components also have additional libraries dependencies, such as TruffleRuby depends on `openssl-dev`.


5. Microsoft Windows

Installing with Microsoft Windows Installer package

1. Double-click the Windows installation file you downloaded. The **Liberica NIK Setup** Wizard opens.
2. Click **Next** on the Welcome screen.



3. On the **Custom Setup** window, choose the features you need. Select a feature to see its description. In most cases, you can use the default setup. Click **Disk Usage** to see the available and required space on your disk. Click **Next**.



4. The package is ready to install. Press **Install**. If you see the User Account Control warning, verify the publisher (BELLSOFT) and click **Yes**.
5. After the installation is complete, click **Finish** to quit the **Liberica NIK Setup Wizard**.

**Note:**

The installer screens above may vary in different releases.

If you want to install Liberica NIK silently, open the command line and run the following command:

```
msiexec /quiet /i bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-windows-  
amd64.msi
```

Liberica NIK is installed to the `C:\Program Files\BellSoft\LibericaNIK-25-OpenJDK-25` directory by default. For scripting purposes, we recommend adding the `$NIK_HOME` environment variable that points to your Liberica Native Image Kit installation directory.

Installing standalone package on Microsoft Windows

To install Liberica NIK as a standalone package on your computer, download the .zip package file and unpack it to a folder. You can also use Windows PowerShell to download and unpack the zip file as follows:

```
Invoke-WebRequest "https://download.bell-sw.com/vm/25.0.1/bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-windows-amd64.zip"
Expand-Archive bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-windows-amd64.zip
-DestinationPath .
```

This will unpack Liberica NIK to the current directory. Either add bin subdirectory to PATH, or remember this directory as the \$NIK_HOME environment variable.

Liberica NIK dependencies on Windows

Microsoft Visual Studio 2017 with Microsoft Visual C++ (MSVC) 15 or later is required for Liberica Native Image Kit.

Start x64 Native Tools Command Prompt to allow native-image and other utilities to find development tools and work from command prompt.

6. Installing language packages

Language packages, such as JS, Python, Wasm, and others can be downloaded from the [Liberica Native Image Kit Download Center](#) and installed as standalone components. To download the package:

1. Scroll down the page to the required OS.
2. Click the **Package** list and then click **Additional Packages**.
3. Click the language package you want to install.
4. Click the download link to the right of the **Package** list.

Once the download is complete, extract the package from zip or tar.gz archive to install it as a standalone component. You can also add `<PACKAGE_DIR>/bin` path to your `PATH` environment variable, where `PACKAGE_DIR` is the language package directory created after extraction.

For example, to install NodeJS package on a Linux OS, download it first and then extract using the following command:

```
tar -zxvf nodejs-java-openjdk25.0.1+14-25.0.1+2-linux-amd64.tar.gz
```

The `nodejs-openjdk25-25.0.1` directory is created. You can use the extracted language pack providing the path to its directory in commands as follows:

```
nodejs-openjdk25-25.0.1/bin/node --version  
v22.17.1
```

You can also add the path to the `nodejs-openjdk25-25.0.1/bin` subdirectory to the `$PATH` variable for the current terminal session if necessary.

```
export PATH=$<NODEJS_PACKAGE_DIR>/bin:$PATH
```

7. Verifying downloaded files

It is a good practice to verify the downloaded installation file by comparing its size on your drive to the size on the [Downloads](#) page.

A more advanced approach is to obtain the checksum of the downloaded file in a command-line interface and compare it to the one you can find next to the Liberica NIK link on the [Downloads](#) page. Check the OS-specific commands below.

Windows

To get the checksum of the downloaded file in the command-line, run the following command in Windows PowerShell. To run PowerShell, open the **Start** menu or press the Windows key + R, type powershell in the **Run** dialog box, and click **OK**.

```
(Get-FileHash .\bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-windows-  
amd64.msi -Algorithm SHA1).Hash
```

Apple macOS

To get the checksum of the downloaded file, use the following command.

```
shasum -a 1 bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-macos-amd64.dmg
```

Linux

To get the checksum of the downloaded file, use the following command. The installation file extension depends on the Linux version.

```
shasum -a 1 bellsoft-liberica-vm-openjdk25.0.1+14-25.0.1+2-linux-amd64.deb
```



Liberica Native Image Kit
25.0.1-2 (25.0.1+14)
Installation Guide

be//soft